



# COVER SHEET REMOVER CSR 2600





## DESCRIPTION

The Rohm and Haas Electronic Materials Cover Sheet Remover model CSR 2600 has been designed and built for installation in a process line. It automatically allows the removal of the mylar from one or both sides of boards. The use of CSR 2600 in-line considerably reduce, both processing times and costs.

## ADVANTAGES

- Easy to use and manage—friendly operation
- High productivity and reliability
- Adjustments for panel thickness or size are not required
- Suitable for innerlayer and rigid panels—full range from 0.17–3.2 mm (0.006–0.125 in.) core thickness
- Completely controlled by PLC—operator interface in local language
- Panel width up to 610 mm (24 inches)
- Preset for automatic in-line operations—easy handshake with other units
- Movable control panel
- Convenient operator access

Overall Dimensions		Panel Size	
Width	1,580 mm (62.2 in.)	Width (min.–max.)	200–610 mm (7.9–24.0 in.)
Length	1,930 mm (76.0 in.)	Length (min.–max.)	200–762 mm (7.9–30.0 in.)
Height (min.–max.)	1,320–1,520 mm (52.0–59.8 in.)	Thickness (min.–max.)	0.17–3.2 mm (0.006–0.125 in.) core thickness
Electrical Requirements		Conveyor (Adjustment)	
Power Type	3 phase; 50/60 Hz + Ground	Conveyor Height	850–1,050 mm (33.5–41.3 in.) (min.–max.)
Power Consumption	2.2 KVA	Conveyor Speed	Adjustable up to 8 m/min. (26 ft./min.)
Nominal Voltage*	400/480/220/200V ±7%		
Compressed Air			
Consumption	25 NI/cycle (0.88 cfm)		
Working Pressure	6 kg/cm (85.3 psi)		
Weight			
Gross	580 kg (1,278 lbs.)		
Net	420 kg (926 lbs.)		
*Different voltage can be provided upon requirement.			