



Panel Corner Turn Table





Panel Corner Turn Table

The Panel Corner Turn Table (PCTT) provides smooth rotation and / or diverting of PCB panels about the vertical line. This unique machine combines the features from the PCR Panel Corner, PTT Panel Turn Table and the PTC Panel Turn Corner – all features from the three machines combined in one machine.

Features

- Smooth rotating and diverting of PCB panels
- Standard profiles – “easy to add” components

Options

- Custom design

Specifications for PCTT

PCB boards		Conveyor		Control	
Min. size	300 x 300 mm	Type	PU rollers	Main supply	230 VAC / 50 Hz
Max. size	635 x 635 mm	Conveyor height	900 – 940 mm	Consumption	200 W
Min. thickness	0.05 mm	Speed	1 – 10 m/min	Air supply	7 Bar / 10 l/min
Max. thickness	6.0 mm	Stroke	4-6 min ⁻¹	PLC	OMRON

Individual specifications	PCTT 25	PCTT 30	Machinery
Conveyor width [mm]	650 mm (inside)	800 mm (inside)	Frame: ITEM aluminium profile system.
Machine dimensions, l [mm]	-	-	Covers: hardened, tinted glass and white powder-coated aluminium plates.
Weight [kg]	200 kg	225 kg	